




## SPECIFICATION

ITEM	SP-1000
OUTPUT POWER	CONTINUOUS POWER 1000W    SURGE POWER 2400W
STANDBY CURRENT	DC 12V < 0.5A    DC 24V < 0.4A
INPUT VOLTAGE	DC12V : 10V~15V    DC24V : 20V~30V
OUTPUT VOLTAGE	AC 100V, 110V, 120V, 220V, 230V, 240V
OUTPUT WAVEFORM	Modified Sine Wave 
EFFICIENCY	> 85%
※ INITIAL CHECKING	AUTO-DETECTING WRONG BATTERY CONT. ex. 12V / 24V
※ OUTPUT REGULATION	± 5% INTELLIGENT PWM
※ OUTPUT FREQUENCY	50Hz, 55Hz, 60Hz CRYSTAL CONTROLLED.
※ COOLING	AUTO-OPERATION FAN
※ OUTPUT SHORT	OUTPUT SHORT CIRCUIT PROTECTION
※ LOW BATTERY	< 10.5V or 21.5V ± 0.5V PRE-ALARM    < 9.5V or 20V ± 0.5V SHUT DOWN & ALARM
※ OVER HEATING	> 60°C PRE-ALARM    > 65°C SHUT DOWN & ALARM
※ OVER LOAD	> 1050W PRE-ALARM    > 1100W SHUT DOWN & ALARM
BATTERY POLARITY REVERSE	BY FUSE
FUSE	DC 12V : 25A * 6PCS    DC 24V : 15A * 6PCS
AC OUTLET	2 AC OUTLETS
DIMENSION (L*W*H)	300*195*80mm
NET WEIGHT	3.1Kg

※ MARK ARE OUR UNIQUE FUNCTIONS