




## SPECIFICATION

ITEM	SP-300
OUTPUT POWER	CONTINUOUS POWER 300W      SURGE POWER 900W
STANDBY CURRENT	DC 12V < 0.4A      DC 24V < 0.3A
INPUT VOLTAGE	DC12V : 10V~15V      DC24V : 20V~30V
OUTPUT VOLTAGE	AC 100V, 110V, 120V, 220V, 230V, 240V
OUTPUT WAVEFORM	Modified Sine Wave 
EFFICIENCY	> 90%
※ INITIAL CHECKING	AUTO-DETECTING WRONG BATTERY CONT. ex. 12V / 24V
※ OUTPUT REGULATION	± 5% INTELLIGENT AVR
※ OUTPUT FREQUENCY	50Hz , 55Hz , 60Hz      CRYSTAL CONTROLLED.
※ COOLING	AUTO-OPERATION FAN
※ OUTPUT SHORT	OUTPUT SHORT CIRCUIT PROTECTION
※ LOW BATTERY	< 10.5V or 21.5V ± 0.5V PRE-ALARM      < 9.5V or 20V ± 0.5V SHUT DOWN & ALARM
※ OVER HEATING	> 60℃ PRE-ALARM      > 65℃ SHUT DOWN & ALARM
※ OVER LOAD	> 350W PRE-ALARM      > 400W SHUT DOWN & ALARM
BATTERY POLARITY REVERSE	BY FUSE
FUSE	DC 12V : 35A * 1PCS      DC 24V : 20A * 1PCS
AC OUTLET	2 AC OUTLETS      EUROPEAN TYPE : 1 AC OUTLET
DIMENSION (L*W*H)	155*73*73mm
NET WEIGHT	0.9Kg

※ MARK ARE OUR UNIQUE FUNCTIONS