



■ Features:

- True sine wave output (THD < 3%)
- Power ON-OFF remote control
- Input & output fully isolation
- Load control cooling fan
- Advanced microprocessor
- Output frequency 50/60 Hz switch selectable
- e-13 / CE / FCC approved
- Input polarity reverse / under voltage / over voltage Protections
- Output short circuit / overload / over temperature protections
- Low power saving mode to conserve (700W~3000W only)
- Tri-color indicators display input, output level & failure Status (700W~3000W only)

Model	SK200	SK350	SK700	SK1000	SK1500	SK2000	SK3000
Rated Output Power	200W	350W	700W	1000W	1500W	2000W	3000W
Surge Power	400W	700W	1400W	2000W	3000W	4000W	6000W
AC Voltage	100 / 110 / 120VAC or 220 / 230 / 240VAC						
AC Waveform	True sine wave (THD < 3%)						
AC Regulation	-3% ~ +5%						
DC Input Voltage	12VDC, 24VDC or 48VDC						
Working Temp.	0 ~ +40°C						
EMC & Safety Standards	100 / 110 / 120 VAC	UL458(For SK350, SK700, SK1000 and SK1500 in "GFCI" RECEPTACLES) ,Compliance to FCC Class A					
	220 / 230 / 240 VAC	Compliance to EN55022 Class A, Compliance to EN61000 - 3 - 2, 3, Compliance to EN60950 - 1					
		Compliance to e-13 *72 / 245 / EEC, 95 / 94 / EC, CISPR 25(2nd edition 2002), ISO 7637-2 : 2004					
Packing	185x147x60mm		296x180x72mm	383x182x88mm	415x191x88mm	422x208x166mm	452x208x166mm
	1.5kg; 6sets 11.5Kg / Carton	1.7kg; 6sets 13Kg / Carton	3kg; 6sets 22Kg / Carton	4kg; 4sets 20Kg / Carton	4.8kg; 4sets 22.5Kg / Carton	8.85kg; 2sets 20.5Kg / Carton	10.2kg; 2sets 23.2Kg / Carton
Warranty	2 years						

*Note:The specifications are subject to change without notice.

Model		SK200-112	SK200-124	SK200-148	SK200-212	SK200-224	SK200-248
Output	LED Indicator	Fault status(RED)					
Input	DC Voltage	12VDC	24VDC	48VDC	12VDC	24VDC	48VDC
	Voltage Range	10.5 ~ 15.0VDC	21.0 ~ 30.0VDC	42.0 ~ 60.0VDC	10.5 ~ 15.0VDC	21.0 ~ 30.0VDC	42.0 ~ 60.0VDC
	Efficiency (Typ.)	89%	91%	92%	91%	93%	94%

Model		SK350-112	SK350-124	SK350-148	SK350-212	SK350-224	SK350-248
Output	LED Indicator	Fault status(RED)					
Input	DC Voltage	12VDC	24VDC	48VDC	12VDC	24VDC	48VDC
	Voltage Range	10.5 ~ 15.0VDC	21.0 ~ 30.0VDC	42.0 ~ 60.0VDC	10.5 ~ 15.0VDC	21.0 ~ 30.0VDC	42.0 ~ 60.0VDC
	Efficiency (Typ.)	89%	91%	92%	91%	93%	91%

Model		SK700-112	SK700-124	SK700-148	SK700-212	SK700-224	SK700-248
Output	LED Indicator	Input voltage level, output load level and fault status					
Input	DC Voltage	12VDC	24VDC	48VDC	12VDC	24VDC	48VDC
	Voltage Range	10.5 ~ 15.0VDC	21.0 ~ 30.0VDC	42.0 ~ 60.0VDC	10.5 ~ 15.0VDC	21.0 ~ 30.0VDC	42.0 ~ 60.0VDC
	Efficiency (Typ.)	89%	91%	92%	91%	93%	94%









Model		SK1000-112	SK1000-124	SK1000-148	SK1000-212	SK1000-224	SK1000-248
Output	LED Indicator	Input voltage level, output load level and fault status					
Input	DC Voltage	12VDC	24VDC	48VDC	12VDC	24VDC	48VDC
	Voltage Range	10.5 ~ 15.0VDC	21.0 ~ 30.0VDC	42.0 ~ 60.0VDC	10.5 ~ 15.0VDC	21.0 ~ 30.0VDC	42.0 ~ 60.0VDC
	Efficiency (Typ.)	89%	92%	93%	91%	93%	94%

Model		SK1500-112	SK1500-124	SK1500-148	SK1500-212	SK1500-224	SK1500-248
Output	LED Indicator	Input voltage level, output load level and fault status					
Input	DC Voltage	12VDC	24VDC	48VDC	12VDC	24VDC	48VDC
	Voltage Range	10.5 ~ 15.0VDC	21.0 ~ 30.0VDC	42.0 ~ 60.0VDC	10.5 ~ 15.0VDC	21.0 ~ 30.0VDC	42.0 ~ 60.0VDC
	Efficiency (Typ.)	88%	91%	92%	90%	93%	94%

Model		SK2000-112	SK2000-124	SK2000-148	SK2000-212	SK2000-224	SK2000-248
Output	LED Indicator	Input voltage level, output load level and fault status					
Input	DC Voltage	12VDC	24VDC	48VDC	12VDC	24VDC	48VDC
	Voltage Range	10.5 ~ 15.0VDC	21.0 ~ 30.0VDC	42.0 ~ 60.0VDC	10.5 ~ 15.0VDC	21.0 ~ 30.0VDC	42.0 ~ 60.0VDC
	Efficiency (Typ.)	89%	92%	93%	91%	94%	95%

Model		SK3000-112	SK3000-124	SK3000-148	SK3000-212	SK3000-224	SK3000-248
Output	LED Indicator	Input voltage level, output load level and fault status					
Input	DC Voltage	12VDC	24VDC	48VDC	12VDC	24VDC	48VDC
	Voltage Range	10.5 ~ 15.0VDC	21.0 ~ 30.0VDC	42.0 ~ 60.0VDC	10.5 ~ 15.0VDC	21.0 ~ 30.0VDC	42.0 ~ 60.0VDC
	Efficiency (Typ.)	88%	91%	92%	90%	93%	94%

■ Output Socket (option)

			
North America (GFCI)	NEMA 5-15R	Continental Europe	IEC-2
			 Solar & Wind energy
Australia / New Zealand	United Kingdom	Universal	

فروشگاه اروین سولار

تلفن: ۰۲۱-۳۳۹۹۹۰۵۶
۰۲۱-۳۳۹۹۹۰۷۲

www.ervinsolar.ir
ervinsolar@hotmail.com