

光伏 连接器金属件



FT 01



FT 02



FT 03



FT 04





FT 05



FT 06



FT-内网



接线盒导电片

Solar DC Connector PV-FT-01



Rated current	30A
Rated voltage	1000VDC(IEC)DC(UL)
Ambient temperature range	-40°C~+90°C(ec)
Degree of protection	IP67 mated IP2X unmated
Contact resistance of plug connectors	0.5mΩ
Contact material	Copper, tin plated
Locking system plug connectors	Snap-in (nur/only MC4)
Flame class	UL94-HB/UL94-VO
Cable Size	2.5mm², 4mm², 6mm²

Solar DC Connector PV-FT-02



Rated current	30A
Rated voltage	1000VDC(IEC)DC(UL)
Ambient temperature range	-40°C~+90°C(ec)
Degree of protection	IP67 mated IP2X unmated
Contact resistance of plug connectors	0.5mΩ
Contact material	Copper, tin plated
Locking system plug connectors	Snap-in (nur/only MC4)
Flame class	UL94-HB/UL94-VO
Cable Size	2.5mm², 4mm², 6mm²

Solar DC Connector PV-FT-03



Rated current	30A
Rated voltage	1500VDC(IEC)DC(UL)
Ambient temperature range	-40°C~+90°C(ec)
Degree of protection	IP67 mated IP2X unmated
Contact resistance of plug connectors	0.5mΩ
Contact material	Copper, tin plated
Locking system plug connectors	Snap-in (nur/only MC4)
Flame class	UL94-HB/UL94-VO
Cable Size	2.5mm², 4mm², 6mm²